



UNIVAP SVC 27-48



UNIVAP SVC 27-48 TECHNICAL DATA

TECHNICAL FEATURES

SOCKETS

Socket-1* (Steam + Vacuum + Detergent)
 Socket-2 (Steam Only)
 Socket-3 (Steam Only)

SOCKET CAPACITY (MAX)

Socket-1
 Socket-2
 Socket-3

OTHER FEATURES

Steam Production
 Colour
 Control System
 Start Up Time
 Cabin Temperature Control
 Cabin Cooling (Double Fan)
 Automatic Filling System
 Water Tank Capacity (Liter)
 Detergent Tank Capacity (Liter)
 Waste Water Tank Capacity (Liter)
 Boiler Material (AISI 304)
 Boiler Volume (Liter)
 Voltage
 Boiler Power
 Boiler Pressure - Temperature
 Boiler Temperature Regulation
 Pressure indicator
 Weight (Machine Only)
 Vacuum Equipment Weight
 Vacuum Power
 Alert Signal
 Dimensions (without vacuum equipment) WxLxH (mm)
 Dimensions (with vacuum equipment) WxLxH (mm)
 Power Cable Length
 Certification

SVC 27

Steam + Detergent
 ✓
 Optional

325 gr/min
 325 gr/min
 670 gr/min

700 gr/min
 Stainless Steel
 PLC (Touch Screen)
 5 min
 ✓
 ✓
 ✓
 30 L
 8 L
 35 L
 ✓
 14.2 L
 380 V
 27 kW
 10 Bar - 185 C°
 ✓
 ✓
 118 kg
 17,2 kg
 3600 W
 ✓
 660x930x1010
 660x930x1550
 Optional
 CE

SVC 48

Steam + Detergent
 ✓
 Standart

610 gr/min
 610 gr/min
 1220 gr/min

1250 gr/min
 Stainless Steel
 PLC (Touch Screen)
 5 min
 ✓
 ✓
 ✓
 30 L
 8 L
 35 L
 ✓
 18.4 L
 400 V
 48 kW
 10 Bar - 185 C°
 ✓
 ✓
 126 kg
 17,2 kg
 3600 W
 ✓
 660x930x1010
 660x930x1550
 Optional
 CE



Socket-1*: Vacuum feature is integrated with the SVC 4.2 and SVC 9-18 models. On SVC 27-48 models vacuum feature is optional and can be added to the machines externally.