

UNIVAP SVC 4.2



UNIVAP SVC 4.2 TECHNICAL DATA

TECHNICAL FEATURES

SOCKETS

Socket-1* (Steam + Vacuum + Detergent) ✓
Socket-2 (Steam Only) ✓
Socket-3 (Steam Only) -

SOCKET CAPACITY (MAX)

Socket-1 80-110 gr/min
Socket-2 80-110 gr/min
Socket-3 -

OTHER FEATURES

Steam Production 110 gr/min
Colour Stainless Steel
Control System PLC
Start Up Time 5 min
Cabin Temperature Control ✓
Cabin Cooling (Double Fan) ✓
Automatic Filling System -
Water Tank Capacity (Liter) 12 L
Detergent Tank Capacity (Liter) 3 L
Waste Water Tank Capacity (Liter) 18 L
Boiler Material (AISI 304) ✓
Boiler Volume (Liter) 3,7 L
Voltage 230-250 V
Boiler Power 4,2 kW
Boiler Pressure - Temperature 10 Bar - 185 °C
Boiler Temperature Regulation ✓
Pressure indicator ✓
Weight (Machine Only) 35 kg
Vacuum Equipment Weight 8 kg
Vacuum Power 1200 W
Alert Signal ✓
Dimensions (without vacuum equipment) WxLxH (mm) 490x650x770
Dimensions (with vacuum equipment) WxLxH (mm) 490x650x1300
Power Cable Length 5 m.
Certification CE

SVC 4.2



Socket-1*: Vacuum feature is integrated with the SVC 4.2 and SVC 9-18 models. On SVC 27-48 models vacuum feature is optional and can be added to the machines externally.