



## UNIVAP SVC 9-18



# UNIVAP SVC 9-18 TECHNICAL DATA

## TECHNICAL FEATURES

### SOCKETS

Socket-1\* (Steam + Vacuum + Detergent)  
 Socket-2 (Steam Only)  
 Socket-3 (Steam Only)

### SOCKET CAPACITY (MAX)

Socket-1 230 gr/min  
 Socket-2 230-310 gr/min  
 Socket-3 -

### OTHER FEATURES

Steam Production	235-470 gr/min
Colour	Stainless Steel
Control System	PLC
Start Up Time	5 min
Cabin Temperature Control	✓
Cabin Cooling (Double Fan)	✓
Automatic Filling System	Optional
Water Tank Capacity (Liter)	18 L
Detergent Tank Capacity (Liter)	5 L
Waste Water Tank Capacity (Liter)	18 L
Boiler Material (AISI 304)	✓
Boiler Volume (Liter)	7.8 L
Voltage	380-400 V
Boiler Power	9 kW-18 kW
Boiler Pressure - Temperature	10 Bar - 185 C°
Boiler Temperature Regulation	✓
Pressure indicator	✓
Weight (Machine Only)	55 kg
Vacuum Equipment Weight	8 kg
Vacuum Power	1200 W
Alert Signal	✓
Dimensions (without vacuum equipment) WxLxH (mm)	580x830x840
Dimensions (with vacuum equipment) WxLxH (mm)	580x830x1380
Power Cable Length	5 m.
Certification	CE

## SVC 9-18



Socket-1\*: Vacuum feature is integrated with the SVC 4.2 and SVC 9-18 models. On SVC 27-48 models vacuum feature is optional and can be added to the machines externally.